

# 各種産業用スリップリングの仕様

品番	回路数	直流(A)								同軸		標準動作電圧(AC)				寸法		内径 DIA"	定格回 転速度 RPM	ページ 番号
		2	5	7	10	14	15	30	50	RG178	RG179	120	240	440	600	DIA" x LG"				
SRA-73540-6	6	6										X				.44 x .64		250	32	
SRA-73540	12	12										X				.44 x .64		250	32	
SRA-73625	18	18										X				.44 x 1.16		100	34	
AC6373-6	6	6										X				.5 x .8		100	36	
AC6373-12	12	12										X				.5 x 1.07		100	36	
SRA-73526	6, 18	X											X			.87 x .57 - 1.11		250	38	
SRA-73528	12	X											X			.87 x .76		250	38	
SRA-73599	24	X											X			.87 x 1.24		250	38	
AC6023-6	6	6											X			.87 x 1.14		250	40	
AC6023-12	12	12											X			.87 x 1.41		250	40	
AC6023-18	18	18											X			.87 x 1.68		250	40	
AC6023-24	24	24											X			.87 x 1.95		250	40	
SRA-73574	36	36											X			.87 x 2.4		250	42	
SRA-73587	28	24				4							X			.87 x 2.4		250	42	
AC6355-36	36	36											X			1 x 2.6		250	44	
AC6355-36V	32	28	4										X			1 x 2.6		250	44	
AC6355-36X	24	20				4							X			1 x 2.6		250	44	
AC6355-36C	26	20	4							2			X			1 x 2.6		250	44	
AC6355-36K	26	20	4								2		X			1 x 2.6		250	44	
AC6355-56	56	56											X			1 x 3.5		250	44	
AC6355-56V	52	48	4										X			1 x 3.5		250	44	
AC6355-56X	44	40				4							X			1 x 3.5		250	44	
AC6355-56C	46	40	4							2			X			1 x 3.5		250	44	
AC6355-56K	46	40	4								2		X			1 x 3.5		250	44	
AC7038	AC6355のIP 65シールドバージョン															1 x 2.6 - 3.6		250	46	
AC6305-6	9	6	3										X			.87 x 1.95		250	47	
AC6305-9	12	9	3										X			.87 x 1.95		250	47	
AC6305-12	15	12	3										X			.87 x 1.95		250	47	
AC6310-3	6	3				3							X			.87 x 1.95		250	47	
AC6310-6	9	6				3							X			.87 x 1.95		250	47	
AC7036	最大80	X	X	X		X				X	X		X	X		3.1 x 3.1 - 6.7		250	49	
EC4294	2 @ 1 amp												X			1.2 x .68		10,000	59	
EC3848-6	6 @ 1 amp												X			1.2 x .98		10,000	59	
EC4199	8 @ 1 amp												X			1.2 x .92		10,000	59	
EC3848-10	10 @ 1 amp												X			1.2 x 1.2		10,000	59	
80050-957 / 1028300-2	2				2									X		1.248 x 2.54		400	51	
80050-958 / 1028300-4	4	2			2									X		1.248 x 2.54		400	51	
80050-956	2						2						X			1.248 x 2.54		400	51	
80050-955	4	2					2						X			1.248 x 2.54		400	51	
80059-950	8						8						X			1.58 x 3.07		600	51	
SRA-73683-6	6	6											X			1.38 x .82	.5	120	9	
SRA-73683-12	12	12											X			1.38 x 1.12	.5	120	9	
SRA-73683-18	18	18											X			1.38 x 1.42	.5	120	9	
SRA-73683-24	24	24											X			1.38 x 1.72	.5	120	9	
AC6438-6	6			6									X			2.1 x 1.6	.5	250	11	
AC6438-12	12			12									X			2.1 x 2.1	.5	250	11	
AC6438-18	18			18									X			2.1 x 2.7	.5	250	11	
AC6438-24	24			24									X			2.1 x 3.2	.5	250	11	

8ページに続く

# 各種産業用スリップリングの仕様

品番	回路数	直流(A)								同軸		標準動作電圧(AC)				寸法	内径	定格回転速度	ページ番号
		2	5	7	10	14	15	30	50	RG178	RG179	120	240	440	600	DIA" x LG"	DIA"	RPM	
AC7094-130	30		30									X				2.17 x 5.02	.5	250	13
AC7094-136	36		36									X				2.17 x 5.57	.5	250	13
AC7094-142	42		42									X				2.17 x 6.13	.5	250	13
AC7094-148	48		48									X				2.17 x 6.69	.5	250	13
AC6349-6	6							6						X		3.07 x 2.9	1	250	15
AC6349-12	12							12						X		3.07 x 4.1	1	250	15
AC6349-18	18							18						X		3.07 x 5.3	1	250	15
AC6349-24	24							24						X		3.07 x 6.5	1	250	15
AC6875		AC6349のIP 65シールドバージョン														3.07 x 2.9 - 6.5	1.0	250	17
AC4598-6	6				6										X	3.9 x 2.13	1.5	250	18
AC4598-12	12				12										X	3.9 x 3.07	1.5	250	18
AC4598-18	18				18										X	3.9 x 4.01	1.5	250	18
AC4598-24	24				24										X	3.9 x 4.94	1.5	250	18
AC6200-12	12	12										X				3.9 x 2.13	1.5	250	20
AC6200-24	24	24										X				3.9 x 3.07	1.5	250	20
AC6200-36	36	36										X				3.9 x 4.01	1.5	250	20
AC6200-48	48	48										X				3.9 x 4.94	1.5	250	20
AC6200-6P/12S	18	12			6							X (2A)	X (10A)			3.9 x 3.07	1.5	250	20
*AC6200-6P/24S	30	24			6							X (2A)	X (10A)			3.9 x 4.01	1.5	250	20
AC6200-6P/36S	42	36			6							X (2A)	X (10A)			3.9 x 4.94	1.5	250	20
AC6200-12P/12S	24	12			12							X (2A)	X (10A)			3.9 x 4.01	1.5	250	20
AC6200-12P/24S	36	24			12							X (2A)	X (10A)			3.9 x 4.94	1.5	250	20
AC6200-18P/12S	30	12			18							X (2A)	X (10A)			3.9 x 4.94	1.5	250	20
AC6419		AC4598およびAC6200シリーズのIP 65シールドバージョン														3.9 x 2.3 - 5.1	1.5	250	22
AC6815	最大128	X	3.5		X							2A/60	3.5A/110	10A/220		4.32 x 3.01 - 5.94	1.5	250	23
AC6428-060	60	60										X				3.9 x 6.6	1.375	250	25
AC6428-072	72	72										X				3.9 x 7.5	1.375	250	25
AC6428-084	84	84										X				3.9 x 8.45	1.375	250	25
AC6428-096	96	96										X				3.9 x 9.34	1.375	250	25
AC6429-006	54	48			6							X (2A)	X (10A)			3.9 x 7.5	1.375	250	25
AC6429-012	60	48			12							X (2A)	X (10A)			3.9 x 7.5	1.375	250	25
AC6231	8							8				X				4.25 x 2.75	1.5	2500	57
AC6275	最大144		X		X				X	X			X (5A)		X	6.63 x 6.6 - 20.5	2.75	1000	27
AC6793		AC6275のIP 65シールドバージョン														6.63 x 6.6 - 20.5	2.75	1000	29
AC6098	最大72				X				X	X					X	8.0 x 4.6 - 14.4	4	250	30
80042-950	8	X											50V			1.52 x 2.29		20,000	53
80043-950	12	X											50V			1.52 x 2.79		20,000	53

\*電力回路と信号回路の組み合わせ構成 注:AC4598、AC6200、AC6349では、回転速度を高速化することができます(オプション)。