

各種産業用スリップリングの仕様

品番	回路数	直流(A)								同軸		標準動作電圧(AC)				寸法 DIA(mm) x LG(mm)	内径 φDIA(mm)	定格回 転速度 RPM	ページ 番号
		2	5	7	10	14	15	30	50	RG178	RG179	120	240	440	600				
SRA-73540-6	6	6										X				11.18 x 16.26		250	41
SRA-73540	12	12										X				11.18 x 16.26		250	41
SRA-73625	18	18										X				11.18 x 29.46		100	43
AC6373-6	6	6										X				12.70 x 20.32		100	45
AC6373-12	12	12										X				12.70 x 27.18		100	45
SRA-73526	6, 18	X											X			22.10 x 14.48 - 28.19		250	47
SRA-73528	12	X											X			22.10 x 19.30		250	47
SRA-73599	24	X											X			22.10 x 31.50		250	47
AC6023-6	6	6											X			22.10 x 28.96		250	49
AC6023-12	12	12											X			22.10 x 35.81		250	49
AC6023-18	18	18											X			22.10 x 42.67		250	49
AC6023-24	24	24											X			22.10 x 49.53		250	49
SRA-73762-12	12	12											X			15.49 x 45.45		250	51
SRA-73762-18	18	18											X			15.49 x 45.45		250	51
SRA-73762-24	24	24											X			15.49 x 45.45		250	51
SRA-73574	36	36											X			22.10 x 60.96		250	53
SRA-73587	28	24			4								X			22.10 x 60.96		250	53
AC6355-36	36	36											X			25.40 x 66.04		250	55
AC6355-36V	32	28	4										X			25.40 x 66.04		250	55
AC6355-36X	24	20			4								X			25.40 x 66.04		250	55
AC6355-36C	26	20	4							2			X			25.40 x 66.04		250	55
AC6355-36K	26	20	4								2		X			25.40 x 66.04		250	55
AC6355-56	56	56											X			25.40 x 88.90		250	55
AC6355-56V	52	48	4										X			25.40 x 88.90		250	55
AC6355-56X	44	40			4								X			25.40 x 88.90		250	55
AC6355-56C	46	40	4							2			X			25.40 x 88.90		250	55
AC6355-56K	46	40	4								2		X			25.40 x 88.90		250	55
AC7038		AC6355のIP 65シールドバージョン														25.40 x 66.04 - 91.44		250	57
AC6305-6	9	6	3										X			22.10 x 49.53		250	58
AC6305-9	12	9	3										X			22.10 x 49.53		250	58
AC6305-12	15	12	3										X			22.10 x 49.53		250	58
AC6310-3	6	3			3								X			22.10 x 49.53		250	58
AC6310-6	9	6			3								X			22.10 x 49.53		250	58
AC7036	最大80	X	X		X		X			X	X		X	X		78.74 x 78.74 - 170.18		250	60
EC4294	2 @ 1 amp												X			30.48 x 17.27		10,000	70
EC3848-6	6 @ 1 amp												X			30.48 x 24.89		10,000	70
EC4199	8 @ 1 amp												X			30.48 x 23.37		10,000	70
EC3848-10	10 @ 1 amp												X			30.48 x 30.48		10,000	70
80050-957 / 1028300-2	2			2										X		31.70 x 64.52		400	62
80050-958 / 1028300-4	4	2		2										X		31.70 x 64.52		400	62
80050-956	2					2								X		31.70 x 64.52		400	62
80050-955	4	2					2							X		31.70 x 64.52		400	62
80059-950	8						8							X		40.13 x 77.98		600	62
SRA-73683-6	6	6												X		35.05 x 20.83	1.27	120	13
SRA-73683-12	12	12												X		35.05 x 28.45	.5	120	13
SRA-73683-18	18	18												X		35.05 x 36.07	.5	120	13
SRA-73683-24	24	24												X		35.05 x 43.69	.5	120	13
AC6438-6	6		6											X		53.34 x 40.64	.5	250	9
AC6438-12	12		12											X		53.34 x 53.34	.5	250	9
AC6438-18	18		18											X		53.34 x 68.58	.5	250	9
AC6438-24	24		24											X		53.34 x 81.28	1.27	250	9

8ページに続く

各種産業用スリップリングの仕様

品番	回路数	直流(A)								同軸		標準動作電圧(AC)				寸法		内径 DIA"	定格回 転速度 RPM	ページ 番号
		2	5	7	10	14	15	30	50	RG178	RG179	120	240	440	600	DIA" x LG"				
AC7094-130	30		30									X				55.12 x 127.51	12.7	250	17	
AC7094-136	36		36									X				55.12 x 141.48	12.7	250	17	
AC7094-142	42		42									X				55.12 x 155.70	12.7	250	17	
AC7094-148	48		48									X				55.12 x 169.93	12.7	250	17	
AC6349-6	6							6						X		77.98 x 73.66	25.4	250	19	
AC6349-12	12							12						X		77.98 x 104.14	25.4	250	19	
AC6349-18	18							18						X		77.98 x 134.62	25.4	250	19	
AC6349-24	24							24						X		77.98 x 165.10	25.4	250	19	
AC6875		AC6349のIP 65シールドバージョン														77.98 x 73.66 - 165.1	25.4	250	21	
AC4598-6	6				6									X		99.06 x 54.10	38.1	250	22	
AC4598-12	12				12									X		99.06 x 77.98	38.1	250	22	
AC4598-18	18				18									X		99.06 x 101.85	38.1	250	22	
AC4598-24	24				24									X		99.06 x 125.48	38.1	250	22	
AC6200-12	12	12										X				99.06 x 54.10	38.1	250	24	
AC6200-24	24	24										X				99.06 x 77.98	38.1	250	24	
AC6200-36	36	36										X				99.06 x 101.85	38.1	250	24	
AC6200-48	48	48										X				99.06 x 125.48	38.1	250	24	
AC6200-6P/12S	18	12			6							X (2A)	X (10A)			99.06 x 77.98	38.1	250	24	
*AC6200-6P/24S	30	24			6							X (2A)	X (10A)			99.06 x 101.85	38.1	250	24	
AC6200-6P/36S	42	36			6							X (2A)	X (10A)			99.06 x 125.48	38.1	250	24	
AC6200-12P/12S	24	12			12							X (2A)	X (10A)			99.06 x 101.85	38.1	250	24	
AC6200-12P/24S	36	24			12							X (2A)	X (10A)			99.06 x 125.48	38.1	250	24	
AC6200-18P/12S	30	12			18							X (2A)	X (10A)			99.06 x 125.48	38.1	250	24	
AC6419		AC4598およびAC6200シリーズのIP 65シールドバージョン														99.06 x 58.42 - 129.54	38.1	250	26	
AC6815	最大128	X	3.5		X							2A/60	3.5A/110	10A/220		109.73 x 76.45 - 150.8	38.1	250	27	
AC6428-060	60	60											X			99.06 x 167.64	34.93	250	29	
AC6428-072	72	72											X			99.06 x 190.50	34.93	250	29	
AC6428-084	84	84											X			99.06 x 214.63	34.93	250	29	
AC6428-096	96	96											X			99.06 x 237.24	34.93	250	29	
AC6429-006	54	48			6							X (2A)	X (10A)			99.06 x 190.50	34.93	250	29	
AC6429-012	60	48			12							X (2A)	X (10A)			99.06 x 190.50	34.93	250	29	
AC6231	8							8					X			107.95 x 69.85	38.1	2500	68	
AC6275	最大144		X		X				X	X				X (5A)		X	168.40 x 167.64 - 520.7	69.85	1000	31
AC6793		AC6275のIP 65シールドバージョン														168.40 x 167.64 - 520.7	69.85	1000	33	
AC6098	最大72				X			X	X						X	203.20 x 116.84 - 365.76	101.6	250	34	
標準Wシリーズ	最大36		X					X		X	X		5A/250		30A	127.00 x 48.01 - 149.61	38.1	60	36	
標準Wシリーズ	最大36		X					X		X	X		5A/250		30A	165.10 x 48.01 - 149.61	76.2	60	36	
プラスWシリーズ	最大124		X					X		X	X		5A/250		30A	127.00 x 61.72 - 263.65	38.1	1000	72	
プラスWシリーズ	最大124		X					X		X	X		5A/250		30A	165.10 x 58.93 - 263.65	76.2	1000	72	
プラスWシリーズ	最大124		X					X		X	X		5A/250		30A	190.50 x 55.37 - 263.65	101.6	600	72	
プラスWシリーズ	最大124		X					X		X	X		5A/250		30A	241.30 x 55.63 - 263.65	152.4	600	72	
プラスWシリーズ	最大124		X					X		X	X		5A/250		30A	317.50 x 61.72 - 263.65	228.6	600	72	
80042-950	8	X											50V			38.61 x 58.17		20,000	64	
80043-950	12	X											50V			38.61 x 70.87		20,000	64	
80038-950	8	2.5											50V			90.42 x 134.11		12,000	74	
80039-950	12	2.5											50V			90.42 x 149.35		12,000	74	
80027-950	24	2.5											50V			90.42 x 219.46		12,000	74	
56814-950	8	8											X			105.00 x 50.01	75.01	250	39	
56871-951	4	4											X			181.99 x 19.99	151.99	250	39	
57165-950	5	5											X			53.39 x 30.99	41.96	250	39	
57622-950	8	8											X			235.99 x 40.01	178.05	150	39	

*電力回路と信号回路の組み合わせ構成 注:AC4598、AC6200、AC6349では、回転速度を高速化することができます(オプション)。